

Hibernation of Mechanical Plant – COVID-19 Pandemic

Essential services in hospitals, food manufacturing, pharmaceuticals and data facilities will remain operational throughout the COVID-19 pandemic.

There are also some facilities (such as commercial buildings) facing temporary Government closures. With the temporary closure, it is imperative to consider steps taken to protect assets from long term damage and ensure human health is not impacted on start-up.

Cooling Tower Systems – Hibernation

Mechanical plant containing water must be continuously protected from corrosion, fouling and bacterial concerns such as Legionella.

Where the decision is to take plant offline, the best protection from corrosion and microbiological growth is to maintain protective water treatment.

Such systems require a minimum of one to two hours of circulation of water through the entire pipework in a 24-hour period.

- The passive corrosion inhibitor layer on metals requires continual replenishing
- Loss of inhibitor will lead to aggressive pitting of steel
- If biocides are not replenished there is potential for corrosion damage through Microbiologically Influenced Corrosion (MIC)
- Stagnant pipework presents a high risk of proliferation of Legionella throughout the system and surrounding environment upon start-up
- Operating circulating pumps are less likely to seize

Cooling Tower Systems – Drain Down

Larger more complex systems are more difficult to drain entirely. The option of draining systems is usually only possible for smaller, simple systems.

Issues to consider:

- Systems that are stored 'dry' will corrode due to water in the atmosphere
- Any components that remain filled will not contain sufficient chemical to prevent corrosion and bacterial growth (including Legionella)
- Potential for seized circulating pumps
- Regulations and Australian Standards require cleaning / disinfection of the cooling tower before start-up
- Shortages of skilled labour on start-up to undertake tower cleaning, disinfection, repair, and/or chemical cleaning

Closed Water Systems

Chilled, closed condenser loops, and heating hot water systems should remain full and circulated at least once a week. They should be monitored at least every three months to ensure the corrosion inhibitor has not been compromised.

Closed systems can experience microbial growth, but this is less an issue and the proposed monitoring time frame should limit any concern.

Important Information

While the information and material included in this document has been formulated with all due care, Hydro-Chem Pty Ltd (HydroChem) does not warrant or represent that the content is free from errors, or omissions or is definitive. HydroChem does not accept liability in relation to the quality, operability or accuracy of the content. Recommendations given by HydroChem are based on tests that have been performed with all due care and are, to the knowledge of HydroChem, reliable. Ultimately, the use of each product by any third party is beyond the control of HydroChem. No guarantee, express or implied is made as to the performance of each product or as to the effects of such or the results to be obtained if not used strictly in accordance with directions, recommendations or established safe practice by any third party. Any third party must assume all responsibility for any loss, damage, cost or expense incurred or arising by reason of any use of the products as such, or in combination with other materials. HydroChem recommends that the products are only used and handled by the buyer under the recommended conditions of use in accordance with established best safe practice.